



## **COURTSCRUBB™ DEEP CLEAN & RECOAT PREP SOLUTION**

COURTSCRUBB™ DEEP CLEAN AND RECOAT PREP SOLUTION is a recoat formulation used to prepare existing waterborne or oil modified finishes for new coatings. COURTSCRUBB™ DEEP CLEAN AND RECOAT PREP SOLUTION minimizes the risk of adhesion failure during the floor recoating process. NONFLAMMABLE

SHAKE WELL BEFORE USING

USE DIRECTLY FROM CONTAINER - DO NOT DILUTE

ALWAYS PREPARE A SAMPLE TEST AREA TO DETERMINE COMPATIBILITY PRIOR TO RECOATING.

SCRUBBING PADS: WHEN THE FLOOR IS SCRUBBED BE SURE TO USE DEFENDER™ BLUE PADS OR STANDARD RED PADS AT A RATE OF 2000 SQUARE FEET PER PAD - 1000 SQUARE FEET EACH SIDE.

ABRADING USING DEFENDER™ BLUE PADS: AFTER THE FLOOR IS SCRUBBED WITH COURTSCRUBB™ DEEP CLEAN AND RECOAT PREP SOLUTION ALLOW THE FLOOR TO DRY. THEN THE FLOOR SHOULD BE ABRADED USING A HEAVY DUTY FLOOR MACHINE EQUIPPED WITH DEFENDER™ BLUE PADS. PADS TO BE ROTATED EVERY 500 SQUARE FEET - 250 SQUARE FEET EACH SIDE.

### **DIRECTIONS :**

**STEP 1 - SCRUB FLOOR USING COURTSCRUBB™ DEEP CLEAN & RECOAT PREP SOLUTION.** Begin by removing all dirt, grit, and dust from the entire court surface by tack and vacuum. Apply COURTSCRUBB™ DEEP CLEAN AND RECOAT PREP SOLUTION in 2' x 50' sections with a mop (do not flood the floor) and scrub using a heavy duty floor machine (175 rpm) equipped with DEFENDER™ BLUE PADS or red pads. This step can also be completed using an autoscrubber if desired. Coverage rate is approximately 2,000 square feet per gallon. Remove the residue by tack and/or squeegee vacuum immediately after each section is scrubbed. Continue across entire surface of court floor and overlap each section to ensure the entire surface has been deep cleaned properly.

**STEP 2 - DRY ABRADE THE ENTIRE FLOOR WITH DEFENDER™ BLUE PADS.** Allow the floor to dry thoroughly before abrading. Using a heavy duty floor machine (175 rpm) abrade the entire court floor dry using DEFENDER™ BLUE PADS. Each pad will effectively abrade 500 square feet, 250 square feet per side. Be sure to space the DEFENDER™ BLUE PADS out systematically and flip them as required for proper abrasion to ensure adhesion of new coatings.

**STEP 3 - TACK AND VACUUM FLOOR.** Vacuum and tack the floor using towels dampened with water. After all debris and dust is removed from the floor prepare final tack using a towel or microfiber pad dampened with COURTSCRUBB™ DEEP CLEAN AND RECOAT PREP SOLUTION. Allow the floor to dry thoroughly and then apply AQUADEFENDER™ WOOD FLOOR FINISH or POLYDEFENDER™ WOOD FLOOR FINISH (see product directions). For best results apply coatings within 2 hours of final tack using COURTSCRUBB™ DEEP CLEAN AND RECOAT PREP SOLUTION.

**DAILY CLEANING:** After your floor recoating project is completed and cured it's important to implement an effective cleaning routine. Dry mop the floor several times during the day to keep the dirt, dust, and grit off the court floor. At the end of each day the floor should be wet mopped using a solution of COURTCLEANZE™ COURT FLOOR CLEANER CONCENTRATE mixed 1 part per 10 parts of water. Wet mopping is very important because it removes the fluids, sweat, and penetrating soils that dry dusting leaves behind. COURTCLEANZE™ COURT FLOOR CLEANER CONCENTRATE can also be used in an autoscrubber or spray and buffed using a heavy duty floor machine (175 PM). SEE PRODUCT INSTRUCTIONS.

### **FOR COMMERCIAL AND INDUSTRIAL USE ONLY**

**CAUTION:** CONTAINS SMALL AMOUNTS OF DIPROYLENE GLYCHOL MONMETHYL ETHER. Do not take internally. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Keep container closed when not in use. Do not store above 100 degrees F. KEEP OUT OF REACH OF CHILDREN.

**FIRST AID:** In case of eye contact, flush immediately with water and get medical attention; for skin wash thoroughly with soap and water. If affected by inhalation, remove to fresh air. If swallowed drink 1-2 glasses of water to dilute. Do not induce vomiting. Get medical attention.

**CLEAN UP:** All tools should be cleaned with water.

**NOTE:** There are no express or implied warranties, including warranties of merchantability or fitness for a particular purpose. Buyers remedies are limited to replacement or refund of purchase price. Manufacturer assumes no liability for injuries, incidental or consequential damages. User shall determine suitability or product for intended use.

BEFORE USING READ ALL DIRECTIONS AND MATERIAL SAFETY DATA SHEETS FOR THIS PRODUCT.